

RS1-1	<h1>REAR PANEL</h1>
Inspection Criteria	
<p>The rear panel should be installed at an outermost position more than the rear fender, tail light housing, etc. to facilitate replacement or repair.</p>	
Reason	
<p>When the rear panel is installed at an outermost position to facilitate replacement or repair, removal or cutting work of the rear fender and other adjacent panels is eliminated, which reduces man-hours and parts cost.</p>	
<div data-bbox="268 763 541 824"><p>Good Example</p></div> <div data-bbox="97 831 730 1279"><p>Damage</p><p>Rear panel</p><p>Rear panel is damaged.</p></div> <div data-bbox="97 1290 730 1738"></div> <div data-bbox="97 1749 730 2085"></div> <div data-bbox="44 2092 780 2197"><p>The adjacent panels did not have to be removed to replace the rear panel because the rear panel was installed in the outermost positon.</p></div>	<div data-bbox="1061 763 1334 824"><p>Poor Example</p></div> <div data-bbox="895 831 1490 1279"><p>Damage</p><p>Rear panel</p><p>Rear panel is damaged.</p></div> <div data-bbox="895 1290 1490 1648"><p>During repair</p></div> <div data-bbox="861 1655 1541 1738"><p>The adjacent panels had to be removed because the rear panel was installed in the inner position.</p></div> <div data-bbox="895 1749 1490 2085"></div> <div data-bbox="861 2092 1541 2197"><p>The left and right adjacent panels were removed so that the rear panel could be replaced.</p></div>